

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE OLD WEST BOUNDARY OF THE

NAVAJO INDIAN RESERVATION,

THE EAST, WEST, AND NORTH BOUNDARIES,

THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS

13, 15, 16, 17, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28 AND 35

IN

**TOWNSHIP 39 SOUTH, RANGE 24 EAST**

OF THE SALT LAKE MERIDIAN

IN THE STATE OF UTAH

EXECUTED BY

**M. Ross Workman,**  
**Cadastral Surveyor**  
**and**  
**C. Scott Bishop,**  
**Survey Technician**

Under special instructions dated **March 21, 2003**, approved **March 21, 2003**,  
which provided for the surveys included under Group Number **956**, and  
assignment instructions dated **May 27, 2003**

Survey commenced **June 3, 2003**  
Survey completed **July 31, 2003**

# INDEX DIAGRAM

Township 39 South, Range 24 East

18	17	16	16	15	14	
13 6	54 5	46 4	40 3	33 2	26 1	9
54	53	45	39	32	25	
13 7	53 8	45 9	39 10	32 11	25 12	9
52	52	44	38	31	24	
12 18	52 17	44 16	37 15	31 14	24 13	8
51	51	43	37	30	23	
12 19	50 20	43 21	36 22	30 23	22 24	7
50	49	42	35	28	21	
11 30	48 29	42 28	35 27	28 26	20 25	6
47	47	41	34	27	19	
10 31	46 32	41 33	33 34	26 35	18 36	6

Navajo Indian Reservation.....	Page	2
The Subdivision of Section 13.....	Page	55
The Subdivision of Section 15.....	Page	56
The Subdivision of Section 16.....	Page	57
The Subdivision of Section 17.....	Page	58
The Subdivision of Section 18.....	Page	59
The Subdivision of Section 20.....	Page	59
The Subdivision of Section 21.....	Page	60
The Subdivision of Section 22.....	Page	61
The Subdivision of Section 23.....	Page	61
The Subdivision of Section 24.....	Page	62
The Subdivision of Section 25.....	Page	63
The Subdivision of Section 26.....	Page	64
The Subdivision of Section 27.....	Page	66
The Subdivision of Section 28.....	Page	66
The Subdivision of Section 35.....	Page	67

## TOWNSHIP 39 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the old west boundary of the Navajo Indian Reservation, the east, west, and north boundaries, the subdivisional lines, and the subdivision of sections 13, 15, 16, 17, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28 and 35, in T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

**History of Surveys**

<b>Surveyed by</b>	<b>Retr. or Resurveyed by</b>
<b>INDIAN RESERVATION BOUNDARY</b>	
Portion R.C. Yundt	1942-44
<b>SOUTH BOUNDARY</b>	
All A.D. Ferron	1884
All	H.D. Page & J.M. Lentz 1899
All	D.B. Miller & J.C. Thoma 1912
	M.D. Cazier 2003
<b>EAST BOUNDARY</b>	
All D.B. Miller & J.C. Thoma	1912
<b>WEST BOUNDARY</b>	
All D.B. Miller & J.C. Thoma	1912
<b>NORTH BOUNDARY</b>	
All D.B. Miller & J.C. Thoma	1912
<b>SUBDIVISION</b>	
All D.B. Miller & J.C. Thoma	1912
Portion	H.W. Miller 1933
Portion	R.C. Yundt 1942-44

## T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 956, dated March 21, 2003.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observations using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations; (CORS) FREDONIA, CARBON COUNTY, and AZTEC. The NAD 83 (CORS96) geographic position of the corner of Townships 39 and 40 South, Ranges 24 and 25 East, is as follows:

Latitude: 37°20'43.704" N.      Longitude: 109°13'21.277" W.

NAD 1983, Elevation: 5044 ft.

---

Dependent Resurvey of a Portion of the  
Old West Boundary of the Navajo Indian Reservation,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey established by  
Robert C. Yundt in 1942-44

---

Beginning at the initial point of the old west boundary of the Navajo Indian Reservation, located on the section line between sections 23 and 26, T. 39 S., R 24 E., monumented with a 3 inch diameter iron post, protruding 10 inches above the ground, in a mound of stone, with brass cap marked:

T 39 S    R 24 E  
S 23    AP 0  
S 26    |    NIR  
1942

Corner is located on gradual northwest slope in scattered sagebrush.

S. 21° 30.3' W., along the old reservation boundary in section 26.

**DEPENDENT RESURVEY OF A PORTION OF THE  
OLD WEST BOUNDARY OF THE NAVAJO INDIAN RESERVATION,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH.**

**CHAINS****39.327**

Angle Point 1, monumented with an iron post, 1 inch diameter, firmly set in a 1 inch drill hole with brass cap marked:

```

      S 26  \
             \
              \
             /  T 39 S
            /    AP 1
           /      NIR
      R 24 E
  
```

1942

From which the original bearing tree:

A piñon, 12 inches diameter bears S. 75° W., 120 links, distance, clearly marked AP 1 BT. (Record: S. 73° 15' W.)

---

S. 10° 30.1' W., along the old reservation boundary in section 26.

- 3.461** Intersect the East - West center line of section 26, not monumented.
- 11.237** Intersect the section line between sections 26 and 27, not monumented.
- 40.601** Mile Post 1, identical with Angle Point 2, monumented with an iron post, 3 inch diameter, protruding 14 inches above ground, firmly set in a mound of stone, with brass cap marked:

```

              AP 2
             /
            /  T 39 S  R 24 E
           /    S 27  NIR
          /      MP 1
         /        1942
        /
       /
      /
     /
    /
   /
  /
 /
/

```

Corner is located among boulders and rocks on east slope.

---

S. 10° 31.8' W., along the 2nd mile of the old reservation boundary in section 27.

- 3.305** Intersect the section line between sections 27 and 34, not monumented.
- 38.540** Point for Angle Point 3, at proportionate distance, there is no remaining evidence of the original corner.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, in a mound of stone, 3 ft. base, to top, of brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE  
OLD WEST BOUNDARY OF THE NAVAJO INDIAN RESERVATION,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

T 39 S R 24 E  
S 34 / NIR  
AP 3  
2003

Corner is located on east point of mesa, in crack of large sandstone ledge.

---

S. 78° 16.5' W., along the old reservation boundary in section 34.

15.006

Angle Point 4, monumented with a 1 inch diameter drill hole, on top of solid sandstone ledge, in the hole,

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, over a magnet, in cement bond, marked:

T 39 S R 24 E  
S 34 / AP 4  
NIR  
2003

S. 39° 12.3' W., along the old reservation boundary in section 34.

21.810

Angle Point 5, monumented with a 1 inch diameter drill hole, on top of solid sandstone ledge, in the hole,

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, over a magnet, in cement bond, marked:

T 39 S R 24 E  
S 34 / AP 5  
NIR  
2003

Corner is located on edge of mesa extending south and east.

---

S. 64° 13.0' W., along the old reservation boundary in section 34.

4.657

Mile Post 2, identical with Angle Point 6, monumented with an 'X', chiseled in top of solid sandstone, at the 'X'.

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on the bedrock, marked:

**DEPENDENT RESURVEY OF A PORTION OF THE  
OLD WEST BOUNDARY OF THE NAVAJO INDIAN RESERVATION,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH.**

CHAINS

T 39 S R 24 E

S 34 / AP 6  
NIR  
MP 2  
2003

Corner is located on edge of mesa extending south and east.

---

S. 37°59.6' W. along the old reservation boundary in section 34.

- 14.165** Point for Angle Point 7, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches into a crack in the sandstone, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S R 24 E  
S 34 / AP 7  
NIR  
2003

Corner is located on the farthest southeast point of mesa.

---

S. 34° 29.5' W., along the old reservation boundary in section 34.

- 14.733** Intersect the south boundary of the township at a point from which, the corner of sections 33 and 34 only, bears N. 89° 58.8' W., 17.364 chains distance, hereinafter described.

From this same point, the 1/4 section corner of section 34 only, bears S. 89° 58.8' E., 22.546 chains distance, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

From this same point, Angle Point 8, bears S. 34° 29.5' W., 12.328 chains distance, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

---

Dependent Resurvey of the East Boundary,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah

---

**DEPENDENT RESURVEY OF THE EAST BOUNDARY  
OLD WEST BOUNDARY OF THE NAVAJO INDIAN RESERVATION,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH.**

**CHAINS**

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

---

From the corner of Townships 39 and 40 South, Ranges 24 and 25 East, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 0° 00.7' E., between sections 31 and 36.

**40.043** Point for the 1/4 section corner of sections 31 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 4 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S	
R 24 E	R 25 E
1/4	
S 36	S 31
2003	

Corner is located on steep northwest slope, 1.5 chains distance from top of ridge bearing North and South. Corner faces and overlooks highway bearing North and South.

**80.086** Point for the corner of sections 25, 30, 31, and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, in a collar of stone, 3 ft. base, to top of brass cap marked:

T 39 S	
R 24 E	R 25 E
S 25	S 30
S 36	S 31
2003	

Corner is located on flat table of black bedrock between two homes.

---

N. 0° 00.7' E., between sections 25 and 30.

**40.043** The 1/4 section corner of sections 25 and 30, which is also the southeast corner of allotment #033377, monumented with a

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

3/4 inch rebar, protruding 11 inches above the ground, in a mound of stone, with an aluminum cap marked:

MANESS  
S 25 1/4 S 30  
1993 COLO LS 19612

This is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, in a collar of stone, 4 ft. base, to top of brass cap marked:

T 39 S  
R 24 E R 25 E  
377 1/4  
S 25 | S 30  
2003

Invert rebar and cap and bury inside the stainless steel post.

Corner is located on flat wash basin in scattered sagebrush and rocky surface.

---

N. 0° 00.2' E., beginning new measurement.

**39.940**

The corner of sections 19, 24, 25, and 30, which is also the northeast corner of allotment #033377, monumented with an iron post, 3 inch diameter, protruding 16 inches above the ground, cemented in corner of fences, extending north and east, with brass cap marked:

T 39 S  
R 24 E R 25 E  
S 24 | S 19 PL  
S 25 | S 30  
NIR  
1912

Add the marks ALOT 377 in southwest quadrant of cap.

Corner is located on steep, rocky, southwest slope in boulders and sage brush.

---

N. 0° 03.9' W., between sections 19 and 24.

**39.949**

The 1/4 section corner of sections 19 and 24, monumented with a mound of stone, 4 ft. base, 3 ft. high, with a hole in the center, this is accepted as the best available evidence of the original corner position.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S  
R 24 E R 25 E  
1/4  
S 24 | S 19  
2003

Corner is located East, 23 links distance from a fence line bearing north and south and falls under an outcropping of a large boulder approximately 40 ft. high.

---

N. 0° 07.7' W., beginning new measurement.

**40.002** Point for the corner of sections 13, 18, 19, and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, with brass cap marked:

T 39 S  
R 24 E R 25 E  
S 13 | S 18  
S 24 | S 19  
2003

Corner is located on west edge of wash draining south, in tamarisk.

Deposit a 2 ft. wooden slab 2 1/2 ft. north of corner to protect monument from washing out.

---

N. 0° 07.7' W., between sections 13 and 18.

**40.002** Point for the 1/4 section corner of sections 13 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S  
R 24 E R 25 E  
1/4  
S 13 | S 18  
2003

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Corner is located in fence line, extending east and west in mixed greasewood and tamarisk.

- 80.004** The corner of sections 7, 12, 13 and 18, monumented with an iron post, 3 inches diameter, protruding 17 inches above the ground, with brass cap marked:

T39S	T39S
R 24 E	R 25 E
S 12	S 7
S 13	S 18
1912	

Corner is located on flat in scattered brush.

---

N. 0° 12.0' W., between sections 7 and 12.

- 40.295** The 1/4 section corner of sections 7 and 12, monumented with an iron post, 1 inch diameter, protruding 14 inches above ground, with brass cap marked:

1/4	
S 12	S 7
1912	

Corner is located on flat drainage in scattered grass and brush. There is a 2 ft. piece of cedar post wired to the corner.

---

N. 0° 05.8' W., beginning new measurement.

- 39.787** The corner of sections 1, 6, 7, and 12, found a 3 inch iron post lying loose on the ground near a mound of stone.

At the corner point

Set iron post to the east of mound of stone, over a magnet, 8 inches in the ground, to solid rock, in a mound of stone, 5 ft. base to top of brass cap marked:

T 39 S	
R 24 E	R 25 E
S 1	S 6
S 12	S 7
1912	

Corner is located on steep southeast rocky slope, 2.000 chains South of ledge, 20 ft. high.

---

N. 0° 08.0' W., between sections 1 and 6.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

**39.988** Point for the 1/4 section corner of sections 1 and 6, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S  
R 24 E R 25 E  
1/4  
S 1 | S 6  
2003

Corner is located on gradual east slope in mixed grass, sage and sparse juniper.

**79.976** The corner of Townships 38 and 39 South, Ranges 24 and 25 East, monumented with a scattered mound of stone with a hole in the center, this is accepted as the best available evidence of the original corner position.

At the corner point (hole in center of mound of stone)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 38 S  
R 24 E R 25 E  
S 36 | S 31  
S 1 | S 6  
T 39 S  
R 24 E R 25 E  
2003

Corner is located 2.000 chains West from edge of mesa, and bears South, 62.7 links distance, from fence line bearing east and west.

---

Dependent Resurvey of the West Boundary,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

---

From the corner of Townships 39 and 40 South, Ranges 23 and 24 East, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0° 05.9' E., between sections 31 and 36.

- 40.068** Point for the 1/4 section corner of sections 31 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, with brass cap marked:

T 39 S
R 23 E   R 24 E
1/4
S 36   S 31
2003

Corner is located West, 30 links distance, from a wash draining northeast.

- 80.136** The corner of sections 25, 30, 31, and 36, monumented with an iron post, 3 inches diameter, set on solid rock, in a mound of stone, 7 ft. base to top of brass cap marked:

T 39 S
R 23 E   R 24 E
S 25   S 30
S 36   S 31
1912

Raise a mound of stone, 4 ft. base, 2 ft. high, east of corner.

N. 0° 04.0' E., between sections 25 and 30.

- 39.988** The 1/4 section corner of sections 25 and 30, monumented with an iron post, 1 inch diameter, protruding 14 inches above ground, with brass cap marked:

1/4
S 25   S 30
1912

N. 0° 03.6' E., beginning new measurement.

- 39.991** The corner of sections 19, 24, 25, and 30, monumented with an iron post, 3 inches diameter, protruding 17 inches above ground, firmly set, with brass cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 39 S	
R 23 E	R 24 E
S 24	S 19
S 25	S 30
1912	

N. 0° 04.1' E., between sections 19 and 24.

- 40.039** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 1 inch diameter, protruding 14 inches above ground, with brass cap marked:

1/4	
S 24	S 19
1912	

N. 0° 04.9' E., beginning new measurement.

- 39.998** The corner of sections 13, 18, 19, and 24, monumented with an iron post, 3 inch diameter, protruding 14 inches above ground, with brass cap marked:

T 39 S	
R 23 E	R 24 E
S 13	S 18
S 24	S 19
1912	

N. 0° 03.6' E., between sections 13 and 18.

- 39.979** The 1/4 section corner of sections 13 and 18, monumented with an iron post, 1 inch diameter, protruding 14 inches above ground, with brass cap marked:

1/4	
S 13	S 18
1912	

N. 0° 01.9' E., beginning new measurement.

- 39.947** The corner of sections 7, 12, 13, and 18, monumented with an iron post, 3 inches diameter, protruding 16 inches above ground, with brass cap marked:

T 39 S	
R 23 E	R 24 E
S 12	S 7
S 13	S 18
1912	

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0° 05.4' E., between sections 7 and 12.

- 39.998** Point for the 1/4 section corner of sections 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S  
R 23 E R 24 E  
1/4  
S 12 | S 7  
2003

Corner is located in center of two track road bearing north and south along a pipeline.

- 79.996** Point for the corner of sections 1, 6, 7, and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S  
R 23 E R 24 E  
S 1 | S 6  
S12 | S 7  
2003

N. 0° 05.4' E., between sections 1 and 6.

- 39.998** The 1/4 section corner of sections 1 and 6, monumented with an iron post, 1 inch diameter, protruding 14 inches above ground, with brass cap marked:

1/4  
S 1 | S 6  
1912

N. 0° 06.3' E., beginning new measurement.

- 40.043** The corner of Townships 38 and 39 South, Ranges 23 and 24 East, monumented with an iron post, 3 inches diameter, protruding 17 inches above the ground, with brass cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 38 S	
R 23 E	R 24 E
S 36	S 31
S 1	S 6
T 39 S	
R 23 E	R 24 E
1912	

Corner is located in sagebrush flat.

---

Dependent Resurvey of the North Boundary,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

---

From the corner of Townships 38 and 39 South, Ranges 24 and 25 East, hereinbefore described.

N. 89° 43.9' W., between sections 1 and 36.

- 40.019** The 1/4 section corner of sections 1 and 36, monumented with a scattered mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 38 S	R 24 E
S 36	
1/4	_____
S 1	
T 39 S	R 24 E
2003	

Corner is located in mixed sagebrush and scattered cedar and bears South, 66 links distance, from fence line bearing east and west.

---

N. 89° 59.8' W., beginning new measurement.

- 40.057** Point for the corner of sections 1, 2, 35, and 36, at proportionate distance, there is no remaining evidence of the original corner position.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 38 S	R 24 E
S 35	S 36
S 2	S 1
T 39 S	R 24 E
2003	

From this corner, the original iron post bears N. 43°28.9' W, 1.172 chains distance, and is cemented in corner of fences extending north and east. This position was not accepted and after a through investigation to the north and east, it was determined that the iron post had been moved at the time the fence was constructed. Add the marks AM on brass cap.

Set a steel fence post alongside.

---

N. 89° 59.8' W., between sections 2 and 35.

40.057

The 1/4 section corner of sections 2 and 35, monumented with a mound of stone, 4 ft. base, with hole in center, and mound of stone to the north, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 38 S	R 24 E
S 35	
1/4	_____
S 2	
T 39 S	R 24 E
2003	

Raise a mound of stone, north of corner.

Corner is located on the rim of a ridge bearing east and west.

---

S. 89° 58.4' W., beginning new measurement.

39.794

The corner of sections 2, 3, 34, and 35, monumented with an iron post, 3 inches diameter, protruding 11 inches above the ground, with brass cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 38 S	R 24 E
S 34	S 35
S 3	S 2
T 39 S	R 24 E

1912

Place a collar of stone around iron post, 3 ft. base to top.

Corner is located West, 50 links distance, from a wash draining southeast.

N. 89° 52.0' W., between sections 3 and 34.

- 39.941** The 1/4 section corner of sections 3 and 34, monumented with an iron post, 1 inch diameter, protruding 10 inches above the ground, in a scattered mound of stone, with brass cap marked:

S 34
1/4
S 3

1912

Corner is located on cedar and sagebrush flat.

N. 89° 58.0' W., beginning new measurement.

- 39.872** The corner of sections 3, 4, 33, and 34, monumented with an iron post, 3 inches diameter, protruding 14 inches above the ground, firmly set in a mound of stone, with brass cap marked:

T 38 S	R 24 E
S 33	S 34
S 4	S 3
T 39 S	R 24 E

1912

Corner is located on a small rim of ledges, southeast, 9 links distance, from a 16 inch diameter juniper tree.

N. 89° 54.0' W., between sections 4 and 33.

- 39.870** The 1/4 section corner of sections 4 and 33, monumented with an iron post, 1 inch diameter, firmly set, protruding 22 inches above the ground, with a mound of stone north, with brass cap marked:

S 33
1/4
S 4

1912

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Place a mound of stone, around iron post, 5 ft. base, 2 ft. high.

Corner is located in small wash draining southwest, in rocky sagebrush and juniper.

---

S. 89° 59.0' W., beginning new measurement.

40.008

The corner of sections 4, 5, 32, and 33, monumented with a mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 38 S	R 24 E
S 32	S 33
S 5	S 4
T 39 S	R 24 E
2003	

Corner is located in small east facing bench, in scattered greasewood and juniper.

---

N. 89° 53.2' W., between sections 5 and 32.

39.898

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base to top of brass cap marked:

T 38 S	R 24 E
S 32	
1/4	_____
S 5	
T 39 S	R 24 E
2003	

Corner is located on west rim in mixed sagebrush and juniper.

79.296

The witness corner for sections 2, 3, 34, and 35, monumented with an iron post, 3 inches diameter, firmly set, protruding 24 inches above the ground, in a scattered mound of stone, with brass cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

	T 38 S	R 24 E
	S 31	S 32
WC	S 6	S 5
	T 39 S	
	1912	

Place a mound of stone around iron post, 3 ft. base, 2 ft. high.

Corner is located on steep north slope.

- 79.796** True point for the corner of sections 5, 6, 31, and 32, at proportionate distance.

N. 89° 48.4' W., between sections 6 and 31.

- 39.963** The 1/4 section corner of sections 6 and 31, monumented with an iron post, 1 inch diameter, protruding 16 inches above the ground, with brass cap marked:

	S 31
1/4	_____
	S 6
	1912

Corner is located on dense sagebrush flat.

S. 89° 53.8' W., beginning new measurement.

- 37.230** The corner of Townships 38 and 39 South, Ranges 23 and 24 East, hereinbefore described.

Dependent Resurvey of the Subdivisional Lines,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

From the corner of sections 1, 2, 35, and 36, on the south boundary, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 0° 12.5' E., between sections 35 and 36.

- 39.954** The 1/4 section corner of sections 35 and 36, monumented with a scattered mound of stone, and a large mound of stone to the west, and is accepted as the best available evidence of the original corner position.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

*CHAINS*

At the corner point (east of large mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, to solid rock, in a mound of stone, 5 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 35 | S 36  
2003

Corner is located in small wash draining northwest, in scattered sagebrush and boulders.

---

N. 0° 19.7' W., beginning new measurement.

**39.854**

The corner of sections 25, 26, 35, and 36, which is also the southeast corner of allotment #033378, and the southwest corner of allotment #033376, monumented with an iron post, 2 inches diameter, protruding 14 inches above ground, firmly set, in a mound of stone, 3 ft. base, with brass cap marked:

T 39 S R 24 E  
S 26 | S 25  
S 35 | S 36  
1912

Add the marks 376 in northeast quadrant of cap, and 378 in northwest quadrant of cap.

Corner is located on north slope of ridge, in scattered sagebrush and boulders.

Raise a mound of stone, 4 ft. base, 2 ft. high, west of corner.

Set a steel fence post alongside.

---

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

N. 89° 52.7' W., between sections 25 and 36.

**40.181**

The 1/4 section corner of sections 25 and 36, which is also the southeast corner of allotment #033376, monumented with a mound of stone, 3 ft. base, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S R 24 E  
376 S 25  
1/4 \_\_\_\_\_  
S 36  
2003

Corner is located on sagebrush flat.

Set a steel fence post alongside.

---

S. 89° 54.7' W., beginning new measurement.

**40.274** The corner of sections 25, 26, 35, and 36.

---

N. 0° 01.4' W., between sections 25 and 26.

**39.856** The 1/4 section corner of sections 25 and 26, which is also the southwest corner of allotment #033375, the northwest corner of allotment #033376, and the northeast corner of allotment #033378, found a 1 inch iron post used as a tension bar in fence corner. Upon further investigation of fence corner, found buried remnants of old fence post, and is accepted as the best available evidence of the original corner position.

At the corner point (fence corner)

Reset the original iron post, over a magnet, 22 inches in the ground, with brass cap marked:

1/4 375  
S 26 | S 25  
378 376  
1912  
2003

Corner is located at corner of fences extending north and east, in sandy greasewood flat.

Set a steel fence post alongside.

---

N. 0° 01.9' W., beginning new measurement.

**20.000** Point for the N 1/16 corner of sections 25 and 26, which is also the southwest corner of allotment #033365, the northwest corner of allotment #033375, and the southeast corner of allotment #033371.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S   R 24 E  
N 1/16  
371      365  
S 26 | S 25  
      375  
2003

Corner is located in sandy wash of Montezuma Creek.

Set a steel fence post alongside.

40.000

Point for the corner of sections 23, 24, 25, and 26, which is also the southwest corner of allotment #033360, the northwest corner of allotment #033365, the northeast corner of allotment #033371 and the southeast corner of allotment #033359, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S   R 24 E  
359      360  
S 23 | S 24  
S 26 | S 25  
371      365  
2003

Corner is located on east edge of Montezuma Creek wash in thick tamarisk.

Set a steel fence post alongside.

---

Reestablishment of the Survey Established  
by D.B. Miller and J.C. Thoma in 1912,  
and the Dependent Resurvey by H.W. Miller in 1933

---

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

S. 89° 56.1' W., between sections 24 and 25.

40.369

The 1/4 section corner of sections 24 and 25, which is also the northwest corner of allotment #033377, the northeast corner of allotment #033365, and the southeast corner of allotment #033360, monumented with an iron post, 1 inch diameter, protruding 8 inches above ground, firmly set, in a

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

mound of stone, 3 ft. base, 2 ft. high to the north, with brass cap marked:

P L  
S 24  
1/4 \_\_\_\_\_  
S 25  
N I R  
1933

Add the marks 377 in southeast quadrant of cap, 365 in southwest quadrant of cap, and 360 in northwest quadrant of cap.

Corner is located on northwest edge of a dry lake bed on rocky slope.

Set a steel fence post alongside.

\_\_\_\_\_

S. 89° 55.0' W., beginning new measurement.

**40.119** The corner of sections 23, 24, 25, and 26.

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

\_\_\_\_\_

N. 0° 06.6' W., between sections 23 and 24.

**40.000** The 1/4 section corner of sections 23 and 24, which is also the northwest corner of allotment #033360, and the northeast corner of allotment #033359, monumented with a scattered mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 23 | S 24  
359      360  
2003

Raise a mound of stone, 2 ft. base, west of corner.

Corner is located in sandy greasewood flat.

Set a steel fence post alongside.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

N.  $0^{\circ} 02.1'$  W., beginning new measurement.

- 40.087** The corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, protruding 16 inches above ground, with brass cap marked:

T 39 S	R 24 E
S 14	S 13
S 23	S 24
1944	

Corner is located West, 2.000 chains distance, from a wash draining southwest.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N.  $89^{\circ} 58.6'$  W., between sections 13 and 24.

- 40.220** Point for the  $1/4$  section corner of sections 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2  $1/2$  inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S	R 24 E
	S 13
$1/4$	_____
	S 24
2003	

Corner is located on sandy flat in mixed sagebrush and greasewood.

The corner is located 50 links South of a barbed wire fence which bears N.  $75^{\circ}$  E. and S.  $75^{\circ}$  W.

- 60.330** Point for the W  $1/16$  section corner of sections 13 and 24.

Set a stainless steel post, 30 inches long, 2  $1/2$  inches diameter, over a magnet, 14 inches in the ground, to solid rock, with brass cap marked:

T 39 S	R 24 E
	S 13
W $1/16$	_____
	S 24
2003	

Corner is located 3 links east from fence corner, in jog of fence line at the base of a large conglomerate boulder.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

**80.440** The corner of sections 13, 14, 23, and 24.

---

N. 0° 08.0' W., between sections 13 and 14.

**19.946** Point for the S 1/16 section corner of sections 13 and 14, not monumented.

**39.892** The 1/4 section corner of sections 13 and 14, monumented with a scattered mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 4 ft. base to top of brass cap marked:

T 39 S R 24 E	
1/4	
S 14	S 13
2003	

Corner is located on gradual west slope in scattered sagebrush and large boulders.

From which:

I chiseled an X BO on a black rock, bearing N. 52° E., 18 links distance.

---

N. 0° 06.3' W., beginning new measurement.

**40.064** The corner of sections 11, 12, 13, and 14, monumented with a 2 inch iron post, protruding 16 inches above ground, and a mound of stone, 3 ft. base, 2 ft. high, west, with brass cap marked:

T 39 S R 24 E	
S 11	S 12
S 14	S 13
1912	

Corner is located South, 1.000 chain distance, from a wash draining southwest.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89° 53.1' W., between sections 12 and 13.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

- 41.188** The 1/4 section corner of sections 12 and 13, monumented with an iron post, 1 inch diameter, protruding 30 inches above ground, in a collar of stone, with brass cap marked:

S 12  
1/4 \_\_\_\_\_  
S 13  
1912

Corner is located on a small ridge bearing north and south, in rabbit brush, sagebrush, and grass.

Rebuild the collar of stone, 5 ft. base, to top of brass cap.

\_\_\_\_\_

N. 89° 53.9' W., beginning new measurement.

- 39.223** The corner of sections 11, 12, 13, and 14.

\_\_\_\_\_

N. 0° 04.9' W., between sections 11 and 12.

- 39.783** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 2 ft. base to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 11 | S 12  
2003

Corner is located East, 1.000 chain distance, from top of round-top hill, in scattered brush and juniper.

- 79.566** The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 inches diameter, in crack of rock, with brass cap marked:

T 39 S R 24 E  
S 2 | S 1  
S 11 | S 12  
1912

Corner is located on west slope of small canyon draining southwest.

\_\_\_\_\_

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

S. 89° 37.4' W., between sections 1 and 12.

- 40.152** Point for the 1/4 section corner of sections 1 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 1  
1/4 —————  
S 12  
2003

- 80.304** The corner of sections 1, 2, 11, and 12.
- 

N. 0° 01.0' E., between sections 1 and 2.

- 40.360** Point for the 1/4 section corner of sections 1 and 2, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 2 | S 1  
2003

Corner is located on west slope, 2.000 chains east from bottom of wash.

- 80.690** The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.
- 

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 0° 09.1' W., between sections 34 and 35.

- 39.943** Point for the 1/4 section corner of sections 34 and 35, which is also the southwest corner of allotment #033379, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 12 inches in the ground, to solid rock, with brass cap marked:

T 39 S R 24 E  
1/4 379  
S 34 | S 35  
2003

Corner is located on steep northeast slope.

Set a steel fence post alongside.

79.886

The corner of sections 26, 27, 34, and 35, which is also the northwest corner of allotment #033379, monumented with an iron post, 2 inches diameter, in a mound of stone, 4 ft. base, with brass cap marked:

T 39 S R 24 E  
S 27 | S 26  
S 34 | S 35  
1942

Add the marks 379 in southeast quadrant of cap.

Corner is located East, 68 links distance, from a wash draining northeast.

Set a steel fence post alongside.

From the corner of sections 25, 26, 35, and 36.

N. 89° 47.7' W., between sections 26 and 35.

39.954

Point for the 1/4 section corner of sections 26 and 35, which is also the southwest corner of allotment #033378, and the northeast corner of allotment #033379, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, in a collar of stone, with brass cap marked:

T 39 S R 24 E  
S 26 378  
1/4 ———  
379 S 35  
2003

Corner is located on east edge of Montezuma Creek wash.

Set a steel fence post alongside.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

**79.908** The corner of sections 26, 27, 34, and 35.

---

N. 0° 11.9' W., between sections 26 and 27.

**32.181** Intersect the Navajo Indian Reservation Boundary between AP 1 and MP 1 (AP 2).

**39.832** The 1/4 section corner of sections 26 and 27, monumented with a scattered mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, to solid rock, in a mound of stone and boulders, 10 ft. base to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 27 | S 26  
2003

Corner is located on steep south slope.

---

N. 0° 04.1' W., beginning new measurement.

**40.043** The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 inches diameter, protruding 12 inches above ground, in a small mound of stone, west, with brass cap marked:

T 39 S R 24 E  
S 22 | S 23  
S 27 | S 26  
1942

Corner is located West, 75 links distance, from wash draining northeast.

I rebuilt mound of stone, 3 ft. base, 2 ft. high, to the west of corner.

---

Reestablishment of the Survey Established by  
D.B. Miller and J.C. Thoma in 1912 and the  
Dependent Resurvey by H.W. Miller in 1933

---

From the corner of sections 23, 24, 25, and 26.

S. 88° 46.0' W., between sections 23 and 26.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

- 8.570** Point for the 1933 Point between sections 23 and 26 determined at record bearing and distance from the X on sandstone outcropping, which bears North, 52 links distance.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

AP  
T 39 S R 24 E  
S 23  
S 26  
2003

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

This will now function as an Angle Point.

---

N. 89° 22.0' W., beginning new measurement.

- 31.377** The 1/4 section corner of sections 23 and 26, which is also the southwest corner of allotment #033359, and the northwest corner of allotment #033371, monumented with an iron post, 1 inch diameter, in a mound of stone, with brass cap marked:

S 23  
1/4           
S 26  
1912

Add the marks 359 in northeast quadrant of cap, and 371 in southeast quadrant of cap.

Corner is located on west slope, 50 links distance from bottom of hill.

Set a steel fence post alongside.

---

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912 and the  
Dependent Resurvey by R.C. Yundt in 1944

---

N. 89° 47.9' W., beginning new measurement.

- 23.557** The initial point of the old Navajo Indian Reservation, hereinbefore described.

- 40.096** The corner of sections 22, 23, 26, and 27.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

---

Reestablishment of the Survey Established by  
D.B. Miller & J.C. Thoma in 1912

---

N. 0° 04.5' W., between sections 22 and 23.

- 40.076** Point for the 1/4 section corner of sections 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 14 inches in the ground, to solid rock, in a mound of stone, 4 ft. base to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 22 | S 23  
2003

Corner is located on west edge of wash draining southwest.

- 80.152** Point for the corner of sections 14, 15, 22, and 23, which is also the southeast corner of allotment #033366, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, with brass cap marked:

T 39 S R 24 E  
366  
S 15 | S 14  
S 22 | S 23  
2003

Set a steel fence post alongside.

---

From the corner of sections 13, 14, 23, and 24.

N. 89° 44.2' W., between sections 14 and 23.

- 40.015** Point for the 1/4 section corner of sections 14 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S R 24 E  
S 14  
1/4 ———  
S 23  
2003

**80.030** The corner of sections 14, 15, 22, and 23.

---

N. 0° 09.4' W., between sections 14 and 15.

**40.076** Point for the 1/4 section corner of sections 14 and 15, which is also the southeast corner of allotment #033368, and the northeast corner of allotment #033366, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
368 1/4  
S 15 | S 14  
366  
2003

Corner is located on east slope in grass and sparse juniper.

Set a steel fence post alongside.

**80.152** Point for the corner of sections 10, 11, 14, and 15, which is also the northeast corner of allotment #033368, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 10 | S 11  
S 15 | S 14  
368  
2003

Set a steel fence post alongside.

---

From the corner of sections 11, 12, 13, and 14.

N. 89° 30.9' W., between sections 11 and 14.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

- 39.997** The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, protruding 21 inches above the ground, oriented to the south, with brass cap marked:

S 11  
1/4 ———  
S 14  
1912

Corner is located in large boulders on south slope, under canopy of 10 inch diameter cedar tree.

---

N. 89° 40.8' W., beginning new measurement.

- 40.071** The corner of sections 10, 11, 14, and 15.
- 

N. 0° 05.9' W., between sections 10 and 11.

- 40.076** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 10 | S 11  
2003

- 80.152** The corner of sections 2, 3, 10, and 11, monumented with a mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
S 3 | S 2  
S 10 | S 11  
2003

Corner is located on a flat bench at edge of wash draining west.

---

From the corner of sections 1, 2, 11, and 12.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

N. 89° 10.7' W., between sections 2 and 11.

- 40.042** Point for the 1/4 section corner of sections 2 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, with brass cap marked:

T 39 S R 24 E  
S 2  
1/4 —————  
S 11  
2003

Corner is located in large grass flat, West, 3.000 chains distance, from a two-track road bearing north and south.

- 80.084** The corner of sections 2, 3, 10, and 11.
- 

N. 0° 07.9' E., between sections 2 and 3.

- 40.005** The 1/4 section corner of sections 2 and 3, monumented with a mound of stone, 4 X 2 X 2 ft., this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 3 | S 2  
2003

Corner is located on flat ledge, West, 23 links distance, from edge.

---

N. 0° 12.2' E., beginning new measurement.

- 39.522** The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.
- 

From the corner of sections 33, and 34 only, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

N. 0° 12.4' W., between sections 33 and 34.

- 40.507** The 1/4 section corner of sections 33 and 34, monumented with a mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 15 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S R 24 E	
1/4	
S 33	S 34
2003	

Corner is located on bottom of draw draining southeast.

---

N. 0° 09.3' W., beginning new measurement.

- 40.063** Point for the corner of sections 27, 28, 33, and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S R 24 E	
S 28	S 27
S 33	S 34
2003	

---

From the corner of sections 26, 27, 34, and 35.

N. 89° 26.4' W., between sections 27 and 34.

- 6.068** Intersect the old Navajo Indian Reservation Boundary between MP 1 (AP 2) and AP 3.

- 39.893** The 1/4 section corner of sections 27 and 34, monumented with a mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S R 24 E  
S 27  
1/4 —————  
S 34  
2003

N. 89° 32.4' W., beginning new measurement.

**39.961** The corner of sections 27, 28, 33, and 34.

N. 0° 29.9' W., between sections 27 and 28.

**40.064** The 1/4 section corner of sections 27 and 28, monumented with an iron post, 1 inch diameter, protruding 20 inches above the ground, loosely set and leaning, with brass cap marked:

1/4  
S 28 | S 27  
1912

I straighten the iron post and place a mound of stone, around iron post, 3 ft. base to top.

Corner is located on steep southeast slope in scattered rocks.

N. 0° 04.4' E., beginning new measurement.

**39.855** The corner of sections 21, 22, 27, and 28 monumented with an iron post, 2 inches diameter, laying loosely on the ground beside a mound of stone.

At the corner point (center of mound)

Reset the iron post, 2 inches diameter, over a magnet, and rebuilt the mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
S 21 | S 22  
S 28 | S 27  
1912

Corner is located on steep east slope on the north edge of a large boulder.

From the corner of sections 22, 23, 26, and 27.

N. 89° 27.7' W., between sections 22 and 27.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

- 39.975** Point for the 1/4 section corner of sections 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
S 22  
1/4 —————  
S 27  
2003

- 79.950** The corner of sections 21, 22, 27, and 28.

N. 0° 03.7' E., between sections 21 and 22.

- 39.993** Point for the 1/4 section corner of sections 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, to bed rock, with brass cap marked:

T 39 S R 24 E  
1/4  
S 21 | S 22  
2003

Raise a small mound of stone, north of corner.

- 79.986** The corner of sections 15, 16, 21, and 22, which is also the southwest corner of allotment #033367, and the southeast corner of allotment #033381, monumented with a mound of stone on solid sandstone, with hole in the center of a mound of stone, and is accepted as the best available evidence of the original corner position.

At the corner point, (center of mound)

Set a brass tablet, 3 1/2 inches diameter, with 3 inch stem over a magnet, in a 1 inch drill hole in solid sandstone, with brass cap marked:

T 39 S R 24 E  
381                      367  
S 16 | S 15  
S 21 | S 22  
2003

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Raise a mound of stone, 3 ft. base 2 ft. high, west of corner.

---

From the corner of sections 14, 15, 22, and 23.

N. 89° 34.7' W., between sections 15 and 22.

- 39.871** Point for the 1/4 section corner of sections 15 and 22, which is also the southwest corner of allotment #033366, and the southeast corner of allotment #033367, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, with brass cap marked:

T 39 S R 24 E  
367 366  
S 15  
1/4 ———  
S 22  
2003

Set a steel fence post alongside.

- 79.742** The corner of sections 15, 16, 21, and 22.
- 

N. 0° 07.5' E., between sections 15 and 16.

- 40.063** The 1/4 section corner of sections 15 and 16, which is also the northwest corner of allotment #033367, and the northeast corner of allotment #033381, monumented with a mound of stone, and a cedar post, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in center of mound, 3 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 16 | S 15  
381 367  
2003

Set a steel fence post alongside.

---

N. 0° 17.4' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

- 19.998** Point for the N 1/16 corner of sections 15 and 16, which is also the southwest corner of allotment #033369.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S	R 24 E
N 1/16	
369	
S 16	S 15
2003	

Corner is located on small bench.

Set a steel fence post alongside.

- 39.996** The corner of sections 9, 10, 15, and 16, which is also the northwest corner of allotment #033369, monumented with an iron post, 2 inches diameter, protruding 22 inches above ground, with brass cap marked:

T 39 S	R 24 E
S 9	S 10
S 16	S 15
1912	

I added the marks 369 in southeast quadrant of cap.

Place a mound of stone around iron post, 3 ft. base to top of brass cap.

Set a steel fence post alongside.

From the corner of sections 10, 11, 14, and 15.

N. 89° 38.7' W., between sections 10 and 15.

- 39.811** Point for the 1/4 section corner of sections 10 and 15, which is also the northwest corner of allotment #033368, and the northeast corner of allotment #033369, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S R 24 E  
S 10  
1/4 —————  
S 15  
369                  368  
2003

Set a steel fence post alongside.

**79.622**      The corner of sections 9, 10, 15, and 16.

---

N. 0° 04.4' W., between sections 9 and 10.

**39.938**      True point for the 1/4 section corner of sections 9 and 10, at proportionate distance, found 1 inch iron post laying on top of sandstone outcropping, with a 90° bend, this point falls at the base of a 22 inch diameter juniper tree, where it is impractical to set a monument,

From which the point selected for an off line witness corner bears N. 70° 20.1' E., 0.220 chains distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to bed rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

W C  
T 39 S R 24 E  
1/4  
S 9 | S 10  
2003

**79.876**      The corner of sections 3, 4, 9, and 10, monumented with an iron post, 2 inches diameter, laying loosely on the ground by a scattered mound of stone, determined the original position of the corner to the east of the mound,

Reset iron post, over a magnet, 10 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
S 4 | S 3  
S 9 | S 10  
1912

Corner is located on east slope 50 links distance, from top of ridge, Indian ruin and pictographs located at top of ridge.

---

From the corner of sections 2, 3, 10, and 11.

N. 89° 51.7' W., between sections 3 and 10.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

*CHAINS*

- 39.761** The 1/4 section corner of sections 3 and 10, monumented with an iron post, 1 inch diameter, protruding 8 inches above the ground, iron post had rusted out,

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 3  
1/4 —————  
S 10  
2003

Corner is located in sandy flat, North, 1.500 chains distance, from main wash, draining southeast.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of corner.

---

N. 89° 49.5' W., beginning new measurement.

- 39.809** The corner of sections 3, 4, 9, and 10.

---

N. 0° 03.8' E., between sections 3 and 4.

- 39.985** The 1/4 section corner of sections 3 and 4, monumented with a large, scattered mound of stone, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 4 inches in the ground, to solid rock, and rebuilt the mound, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 4 | S 3  
2003

Corner is located on rocky southwest slope, North, 75 links distance, from wash draining northwest.

---

N. 0° 06.1' W., beginning new measurement.

- 39.440** The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

---

From the corner of sections 32 and 33 only, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 0° 00.1' E., between sections 32 and 33.

- 40.005** The 1/4 section corner of sections 32 and 33, monumented with a mound of stone, 3 ft. base, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E
1/4
S 32   S 33
2003

Corner is located on north edge of wash draining northeast.

---

N. 0° 09.7' E., beginning new measurement.

- 39.825** The corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 inches diameter, loosely set, in a mound of stone, straightened post, in a mound of stone, 3 ft. base, with brass cap marked:

T 39 S R 24 E
S 29   S 28
S 32   S 33
1912

Corner is located on steep south slope.

---

From the corner of sections 27, 28, 33, and 34.

S. 89° 21.5' W., between sections 28 and 33.

- 39.949** Point for the 1/4 section corner of sections 28 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 6 ft. base, to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S R 24 E  
S 28  
1/4 —————  
S 33  
2003

Corner is located on southwest slope among boulders.

**79.898** The corner of sections 28, 29, 32, and 33.

---

N. 0° 14.8' W., between sections 28 and 29.

**40.342** The 1/4 section corner of sections 28 and 29, monumented with an iron post, 1 inch diameter, protruding 17 inches above ground, with brass cap marked:

1/4  
S 29 | S 28  
1912

---

N. 0° 08.9' W., beginning new measurement.

**39.644** The corner of sections 20, 21, 28, and 29, monumented with an iron post, 2 inches diameter, in a mound of stone, with brass cap marked:

T 39 S R 24 E  
S 20 | S 21  
S 29 | S 28  
1912

Raise a mound of stone around iron post, 7 ft. base, to top.

---

From the corner of sections 21, 22, 27, and 28.

S. 89° 24.4' W., between sections 21 and 28.

**39.931** Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 21  
1/4 —————  
S 28  
2003

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Raise a mound of stone, 4 ft. base, 3 ft. high, north of corner.

**79.862** The corner of sections 20, 21, 28, and 29.

---

N. 0° 07.2' E., between sections 20 and 21.

**40.126** Point for the 1/4 section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, on top of cross chiseled on sandstone, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 20 | S 21  
2003

Corner is located on north edge of sandstone ledges, in scattered juniper.

**80.252** The corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 inches diameter, firmly set, with brass cap marked:

T 39 S R 24 E  
S 17 | S 16  
S 20 | S 21  
1912

Corner is located under an overhang.

---

From the corner of sections 15, 16, 21, and 22.

S. 89° 35.8' W., between sections 16 and 21.

**39.881** Point for the 1/4 section corner of sections 16 and 21, which is also the southwest corner of allotment #033381, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S R 24 E  
S 16 381  
1/4 —————  
S 21  
2003

Set a steel fence post alongside.

**79.762** The corner of sections 16, 17, 20, and 21.

---

N. 0° 01.0' W., between sections 16 and 17.

**39.945** Point for the 1/4 section corner of sections 16 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 17 | S 16  
2003

Corner is located on east slope in scattered grass, sagebrush, and juniper.

**79.890** Point for the corner of sections 8, 9, 16, and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 8 | S 9  
—————  
S 17 | S 16  
2003

---

From the corner of sections 9, 10, 15, and 16.

S. 89° 28.5' W., between sections 9 and 16.

**39.828** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, in a mound of stone, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S   R 24 E  
S   9  
1/4 —————  
S 16  
2003

**79.656**      The corner of sections 8, 9, 16, and 17.

---

N. 0° 03.1' W., between sections 8 and 9.

**39.945**      Point for the 1/4 section corner of sections 8 and 9, at proportionate distance, found 1 inch iron post lying loose on the ground,

Set iron post, over a magnet, 30 inches in the ground, with brass cap marked:

1/4  
S 8 | S 9  
2003  
1912

**79.890**      The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 inches diameter, protruding 20 inches above ground, with brass cap marked:

T 39 S   R 24 E  
S 5 | S 4  
S 8 | S 9  
1912

---

From the corner of sections 3, 4, 9, and 10.

S. 89° 51.1' W., between sections 4 and 9.

**39.838**      The 1/4 section corner of sections 4 and 9, monumented with an iron post, 1 inch diameter, loosely set, in a mound of stone, I rebuilt the mound of stone, 4 ft. base, to top of brass cap marked:

S 4  
1/4 —————  
S 9  
1912

Corner is located on a gradual east slope in cedar, sage brush and greasewood.

---

S. 89° 07.0' W., beginning new measurement.

**39.774**      The corner of sections 4, 5, 8, and 9.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

*CHAINS*

---

N. 0° 13.4' W., between sections 4 and 5.

- 40.042** Point for the 1/4 section corner of sections 4 and 5, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
1/4  
S 5 | S 4  
2003

- 80.063** The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.
- 

From the corner of sections 31 and 32 only, on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 1° 21.8' W., between sections 31 and 32.

- 39.998** The 1/4 section corner of sections 31 and 32, monumented with a mound of stone, 3 ft. base, this is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 31 | S 32  
2003

---

N. 0° 06.3' E., beginning new measurement.

- 39.981** The corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 inch diameter, protruding 12 inches above ground, in a collar of stone, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S	R 24 E
S 30	S 29
S 31	S 32
1912	

---

From the corner of sections 28, 29, 32, and 33.

N. 89° 59.8' W., between sections 29 and 32.

- 40.072** The 1/4 section corner of sections 29 and 32, monumented with a 1/2 inch rebar, 18 inches long, with 1 inch aluminum cap marked:

THOMAS
29
———— 1/4
32
PE-LS 6728

This is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a mound of stone, 5 ft. base, to top of brass cap marked:

T 39 S	R 24 E
S 29	
1/4 ———	
S 32	
2003	

Invert rebar and cap, bury inside stainless steel post.

Set a steel fence post alongside.

---

S. 89° 57.4' W., beginning new measurement.

- 40.063** The corner of sections 29, 30, 31, and 32.

---

N. 89° 44.4' W., between sections 30 and 31.

- 39.928** Point for the 1/4 section corner of sections 30 and 31, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 30  
1/4 ———  
S 31  
2003

Corner is located on west slope, 22 links distance, from top of spur.

78.039

The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 29, 30, 31, and 32.

N. 0° 01.5' E., between sections 29 and 30.

40.086

The 1/4 section corner of sections 29 and 30, monumented with a 1/2 inch rebar, 18 inches long, with 1 inch aluminum cap marked:

THOMAS  
30 | 29  
1/4  
PE-LS 6728

This is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 30 | S 29  
2003

Invert rebar and cap, bury inside stainless steel post.

Raise a mound of stone, 3 ft. base, west of corner.

Set a steel fence post alongside.

---

N. 0° 04.5' E., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

**39.963** Point for the corner of sections 19, 20, 29, and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E	
S 19	S 20
S 30	S 29
2003	

Corner is located West, 2.000 chains distance, from a two-track road bearing north and south.

---

From the corner of sections 20, 21, 28, and 29.

N. 89° 52.9' W., between sections 20 and 29.

**39.907** The 1/4 section corner of sections 20 and 29, monumented with a 1/2 inch rebar, 18 inches long, with 1 inch aluminum cap marked:

THOMAS	
S 20	
1/4	_____
S 29	
PE-LS 6728	

This is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E	
S 20	
1/4	_____
S 29	
2003	

Invert rebar and cap, bury inside stainless steel post.

Set a steel fence post alongside.

---

S. 89° 56.0' W., beginning new measurement.

**39.865** The corner of sections 19, 20, 29, and 30.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

*CHAINS*

---

N. 89° 47.5' W., between sections 19 and 30.

- 39.952** Point for the 1/4 section corner of sections 19 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 19  
1/4 —————  
S 30  
2003

Corner is located on west edge of wash, draining southwest.

Raise a mound of stone, 2 ft. base, north of the corner.

- 78.006** The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.
- 

From the corner of sections 19, 20, 29, and 30.

N. 0° 00.6' E., between sections 19 and 20.

- 39.963** Point for the 1/4 section corner of sections 19 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 19 | S 20  
2003

Corner is located inside fenced lot of abandoned house, 8 links distance from an old Chevy flatbed truck.

- 79.926** Point for the corner of sections 17, 18, 19, and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S	R 24 E
S 18	S 17
S 19	S 20
2003	

---

From the corner of sections 16, 17, 20, and 21.

S. 89° 47.6' W., between sections 17 and 20.

- 39.955** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 10 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S	R 24 E
S 17	
1/4	_____
S 20	
2003	

- 79.910** The corner of sections 17, 18, 19, and 20.

---

N. 89° 42.6' W., between sections 18 and 19.

- 40.016** Point for the 1/4 section corner of sections 18 and 19, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S	R 24 E
S 18	
1/4	_____
S 19	
2003	

Corner is located South, 60 links distance, from a dirt road bearing east and west, and North, 73 links distance, from a power line bearing east and west.

- 77.901** The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

N. 0° 01.2' E., between sections 17 and 18.

- 39.963** Point for the 1/4 section corner of sections 17 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E
1/4
S 18   S 17
2003

Corner is located North, 30 links distance, from a two-track road.

- 79.926** The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 inches diameter, protruding 17 inches above ground, with brass cap marked:

T 39 S R 24 E
S 7   S 8
S 18   S 17
1912

---

From the corner of sections 8, 9, 16, and 17.

S. 89° 49.1' W., between sections 8 and 17.

- 39.922** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E
S 8
1/4 ———
S 17
2003

- 79.844** The corner of sections 7, 8, 17, and 18.
- 

N. 89° 42.6' W., between sections 7 and 18.

- 39.994** Point for the 1/4 section corner of sections 7 and 18, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 7  
1/4 —————  
S 18  
2003

- 77.849** The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 7, 8, 17, and 18.

N. 0° 15.9' E., between sections 7 and 8.

- 40.056** Point for the 1/4 section corner of sections 7 and 8, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
1/4  
S 7 | S 8  
2003

- 80.112** Point for the corner of sections 5, 6, 7, and 8, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 6 | S 5  
—|—  
S 7 | S 8  
2003

---

From the corner of sections 4, 5, 8, and 9.

S. 89° 58.7' W., between sections 5 and 8.

- 39.693** Point for the 1/4 section corner of sections 5 and 8, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with brass cap marked:

T 39 S R 24 E  
S 5  
1/4 —————  
S 8  
2003

Corner is located North, 6 links distance, from a wash draining northwest.

**79.386** The corner of sections 5, 6, 7, and 8.

---

S. 89° 47.4' W., between sections 6 and 7.

**39.772** The 1/4 section corner of sections 6 and 7, monumented with an iron post, 1 inch diameter, protruding 18 inches above ground, with brass cap marked:

S 6  
1/4 —————  
S 7  
1912

---

N. 89° 22.0' W., beginning new measurement.

**38.310** The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 7, and 8.

N. 1° 03.0' W., between sections 5 and 6.

**40.063** The 1/4 section corner of sections 5 and 6, monumented with a 1 inch iron post, protruding 20 inches above ground, with brass cap marked:

1/4  
S 6 | S 5  
1912

---

N. 0° 00.2' W., beginning new measurement.

**40.194** True point for the corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

**THE SUBDIVISION OF SECTION 13,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

---

The Subdivision of Section 13,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 13 and 24.

N. 0° 49.7' W., on the North and South center line of section 13.

**19.976** Point for the Center S 1/16 section corner of section 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 10 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

T 39 S R 24 E  
C  
S 1/16 | S 13  
C  
2003

**39.952** Point for the Center 1/4 section corner of section 13, at intersection of the East - West center line of section 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
C 1/4  
S 13  
2003

Corner is located on steep north slope.

**79.913** The 1/4 section corner of sections 12 and 13.

---

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89° 56.8' W., on the East - West center line of section 13.

**40.704** The Center 1/4 section corner of section 13.

**60.570** Point for the Center W 1/16 section corner of section 13, not monumented.

**80.436** The 1/4 section corner of sections 13 and 14.

---

**THE SUBDIVISION OF SECTION 13,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the W 1/16 section corner of sections 13 and 24

N. 0° 28.9' W., on the North - South center line of the Southwest 1/4 of section 13.

- 19.961** Point for the SW 1/16 section corner of section 13, at intersection of the East - West center line of the SW 1/4 of section 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, on top of solid rock, in a mound of stone, 5 ft. base, to top of brass cap marked:

T 39 S R 24 E  
SW 1/16  
S 13  
2003

- 39.922** The point for Center W 1/16 section corner of section 13.
- 

From the Center S 1/16 section corner of section 13.

S. 89° 59.1' W., on the East - West center line of the SW 1/4 of section 13.

- 19.988** The SW 1/16 section corner of section 13.

- 39.976** The point for the S 1/16 section corner of sections 13 and 14.
- 

The Subdivision of Section 15,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 15 and 22.

N. 0° 07.2' W., on the North - South center line of section 15.

- 40.070** Point for the Center 1/4 section corner of section 15, which is also the southwest corner of allotment #033368, the northwest corner of allotment #033366, and the northeast corner of allotment #033367, at intersection of the East - West center line of section 15,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

**THE SUBDIVISION OF SECTION 15,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

T 39 S   R 24 E  
368  
C 1/4   S 15  
367   366  
2003

Set a steel fence post alongside.

Corner is located on flat rocky ground.

- 60.088** Point for the Center N 1/16 section corner of section 15, which is also the southeast corner of allotment #033369, and on the west line of allotment #033368.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 1 inch in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S   R 24 E  
369   C   368  
N 1/16 | S 15  
C  
2003

Corner falls on top of cedar and sage covered mesa.

- 80.106** The 1/4 section corner of sections 10 and 15.
- 

From the 1/4 section corner of sections 14 and 15.

N. 89° 35.2' W., on the East - West center line of section 15.

- 39.841** The Center 1/4 section corner of section 15.

- 79.537** The 1/4 section corner of sections 15 and 16.
- 

From the Center N 1/16 section corner of section 15.

N. 89° 36.9' W., on the East - West center line of the NW 1/4 of section 15.

- 39.754** The N 1/16 section corner of sections 15 and 16.
- 

The Subdivision of Section 16,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 16 and 21.

N. 0° 03.0' W., on the North - South center line of section 16.

**THE SUBDIVISION OF SECTION 16,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

**40.004** Point for the Center 1/4 section corner of section 16, which is also the northwest corner of allotment #033381, at intersection of the East - West center line of section 16.

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T 39 S R 24 E  
C 1/4  
S 16  
381  
2003

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

Set a steel fence post alongside.

**79.974** The 1/4 section corner of sections 9 and 16.

---

From the 1/4 section corner of sections 15 and 16.

N. 89° 30.7' W., on the East - West center line of section 16.

**39.999** The center 1/4 section corner of section 16.

**79.854** The 1/4 section corner of sections 16 and 17.

---

The Subdivision of Section 17,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 17 and 20.

N. 0° 00.1' E., on the North - South center line of section 17.

**39.954** Point for the Center 1/4 section corner of section 17, at intersection of the East - West center line of section 17,

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T 39 S R 24 E  
C 1/4  
S 17  
2003

**THE SUBDIVISION OF SECTION 17,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

## CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high. west of corner.

**79.908** The 1/4 section corner of sections 8 and 17.

---

From the 1/4 section corner of sections 16 and 17.

S. 89° 48.4' W., on the East - West center line of section 17.

**39.939** The center 1/4 section corner of section 17.

**79.878** The 1/4 section corner of sections 17 and 18.

---

The Subdivision of Section 18,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 18 and 19.

N. 0° 01.7' E., on the North - South center line of section 18.

**39.971** Point for the Center 1/4 section corner of section 18, at intersection of the East - West center line of section 18,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E  
C 1/4  
S 18  
2003

**79.926** The 1/4 section corner of sections 7 and 18.

---

From the 1/4 section corner of sections 17 and 18.

N. 89° 41.9' W., on the East - West center line of section 18.

**40.005** The center 1/4 section corner of section 18.

**77.865** The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 20,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 20 and 29.

**THE SUBDIVISION OF SECTION 20,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

N. 0° 04.8' E., on the North - South center line of section 20.

- 39.980** Point for the Center 1/4 section corner of section 20, at intersection of the East - West center line of section 20.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, with brass cap marked:

T 39 S R 24 E  
C 1/4  
S 20  
2003

Corner is located on gradual east slope.

- 80.024** The 1/4 section corner of sections 17 and 20.
- 

From the 1/4 section corner of sections 20 and 21.

S. 89° 54.5' W., on the East - West center line of section 20.

- 39.931** The center 1/4 section corner of section 20.

- 79.841** The 1/4 section corner of sections 19 and 20.
- 

The Subdivision of Section 21,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 21 and 28.

N. 0° 05.5' E., on the North - South center line of section 21.

- 40.059** Point for the Center 1/4 section corner of section 21, at intersection of the East - West center line of section 21,
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E  
C 1/4  
S 21  
2003

Corner is located in a small draw draining southeast.

- 80.118** The 1/4 section corner of sections 16 and 21.
-

**THE SUBDIVISION OF SECTION 21,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the 1/4 section corner of sections 21 and 22.

S. 89° 30.1' W., on the East - West center line of section 21.

**39.906** The center 1/4 section corner of section 21.

**79.812** The 1/4 section corner of sections 20 and 21.

---

The Subdivision of Section 22,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 22 and 27.

N. 0° 00.4' W., on the North - South center line of section 22.

**40.035** Point for the Center 1/4 section corner of section 22, at intersection of the East - West center line of section 22,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

T 39 S R 24 E  
C 1/4  
S 22  
2003

**80.070** The 1/4 section corner of sections 15 and 22.

---

From the 1/4 section corner of sections 22 and 23.

N. 89° 31.2' W., on the East - West center line of section 22.

**39.923** The center 1/4 section corner of section 22.

**79.846** The 1/4 section corner of sections 21 and 22.

---

The Subdivision of Section 23,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 23 and 26.

N. 0° 07.7' W., on the North - South center line of section 23.

**40.027** Point for the Center 1/4 section corner of section 23, which is also the northwest corner of allotment #033359, at intersection of the East - West center line of section 23.

THE SUBDIVISION OF SECTION 23,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 6 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top of brass cap marked:

T 39 S R 24 E  
C 1/4  
S 23  
359  
2003

Corner is located on east slope.

Set a steel fence post alongside.

**80.109** The 1/4 section corner of sections 14 and 23.

---

From the 1/4 section corner of sections 23 and 24.

N. 89° 43.7' W., on the East - West center line of section 23.

**39.953** The center 1/4 section corner of section 23.

**80.009** The 1/4 section corner of sections 22 and 23.

---

The Subdivision of Section 24,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 24 and 25.

N. 0° 00.3' E., on the North - South center line of section 24.

**39.969** Point for the Center 1/4 section corner of section 24, which is also the northeast corner of allotment # 033360, at intersection of the East - West center line of section 24,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

T 39 S R 24 E  
C 1/4  
S 24  
360  
2003

Set a steel fence post alongside.

**80.013** The 1/4 section corner of sections 13 and 24.

THE SUBDIVISION OF SECTION 24,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

---

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

S. 89° 57.8' W., on the East - West center line of section 24.

**40.317** The center 1/4 section corner of section 24.

**80.513** The 1/4 section corner of sections 23 and 24.

---

The Subdivision of Section 25,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 25 and 36.

N. 0° 08.0' W., on the North - South center line of section 25.

**39.876** Point for the Center 1/4 section corner of section 25, which is also the southwest corner of allotment #033377, the northeast corner of allotment #033376, and the southeast corner of allotment #033375, at intersection of the East - West center line of section 25,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, with brass cap marked:

T 39 S R 24 E  
375 377  
C 1/4  
S 25  
376  
2003

Raise a mound of stone, 4 ft. base, 3 ft. high, west of corner.

Steel fence post alongside.

**59.864** Point for the Center N 1/16 section corner of section 25, which is also the northeast corner of allotment #033375, the southeast corner of allotment #033365, and the west boundary of allotment #033377.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with brass cap marked:

THE SUBDIVISION OF SECTION 25,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 39 S R 24 E  
365 C 377  
N 1/16 | S 25  
375 C 377  
2003

Set a steel fence post alongside.

**79.852** The 1/4 section corner of sections 24 and 25.

---

From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.

S. 89° 53.0' W., on the East - West center line of section 25.

**40.278** The center 1/4 section corner of section 25.

**80.471** The 1/4 section corner of sections 25 and 26.

---

From the Center N 1/16 section corner of section 25.

S. 89° 54.0' W., on the East - West center line of the Northwest 1/4 of section 25.

**40.157** The N 1/16 section corner of sections 25 and 26.

---

The Subdivision of Section 26,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 26 and 35.

N. 0° 01.5' W., on the North - South center line of section 26.

**39.844** True point for the Center 1/4 section corner of section 26, which is also the northwest corner of allotment #033378, at intersection of the East - West center line of section 26, falls in a deep wash draining east, where it is impractical to set a monument,

From which the point selected for the off line witness corner bears S 31° 50.6' W, 1.105 chains distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a collar of stone, 2 ft. base, to top of brass cap marked:

THE SUBDIVISION OF SECTION 26,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

W C  
T 39 S R 24 E  
C 1/4  
S 26  
378  
2003

Set a steel fence post alongside.

- 59.860** Point for the Center N 1/16 section corner of section 26, which is also the southwest corner of allotment #033371.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to solid rock, with brass cap marked:

T 39 S R 24 E  
C 371  
N 1/16 | S 26  
C  
2003

Corner is located West, 50 links distance, from a two-track road, bearing north and south.

Set a steel fence post alongside.

- 79.876** The 1/4 section corner of sections 23 and 26.

---

From the 1/4 section corner of sections 25 and 26.

N. 89° 48.8' W., on the East - West center line of section 26.

- 39.952** The true point for the center 1/4 section corner of section 26.

- 78.579** Intersect the old Navajo Indian Reservation Boundary between AP 1 and MP 1 (AP 2).

- 80.023** The 1/4 section corner of sections 26 and 27.

---

From the N 1/16 section corner of sections 25 and 26.

N. 89° 47.4' W., on the East - West center line of the Northeast 1/4 of section 26.

- 39.949** The Center N 1/16 section corner of section 26.

---

The Subdivision of Section 27,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

THE SUBDIVISION OF SECTION 27,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 27 and 34.

N.  $0^{\circ} 11.9'$  W., on the North - South center line of section 27.

- 39.911** True point for the Center 1/4 section corner of section 27, at intersection of the East - West center line of section 27, falls in a wash draining southeast, where it is impractical to set a monument,

From which the point selected for the off line witness corner bears S  $21^{\circ} 10.2'$  W, 0.073 chains distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 14 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of brass cap marked:

W C  
T 39 S R 24 E  
C 1/4  
S 27  
2003

- 79.862** The 1/4 section corner of sections 22 and 27.
- 

From the 1/4 section corner of sections 26 and 27.

N.  $89^{\circ} 19.6'$  W., on the East - West center line of section 27.

- 39.890** The true point for the center 1/4 section corner of section 27.

- 80.059** The 1/4 section corner of sections 27 and 28.
- 

The Subdivision of Section 28,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 28 and 33.

N.  $0^{\circ} 12.3'$  W., on the North - South center line of section 28.

- 40.203** Point for the Center 1/4 section corner of section 28, at intersection of the East - West center line of section 28,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with brass cap marked:

THE SUBDIVISION OF SECTION 28,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 39 S R 24 E  
C 1/4  
S 28  
2003

Corner is located East, 50 links distance, from a two-track road, bearing Northeast and Southwest.

**79.952** The 1/4 section corner of sections 21 and 28.

---

From the 1/4 section corner of sections 27 and 28.

S. 89° 33.4' W., on the East - West center line of section 28.

**39.739** The center 1/4 section corner of section 28.

**79.712** The 1/4 section corner of sections 28 and 29.

---

The Subdivision of Section 35,  
T. 39 S., R. 24 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 2 and 35, on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set with brass cap marked, as described in the concurrent resurvey of Township 40 South, Range 24 East.

N. 0° 06.3' W., on the North - South center line of section 35.

**39.949** Point for the Center 1/4 section corner of section 35, which is also the southeast corner of allotment #033379, at intersection of the East - West center line of section 35,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, with brass cap marked:

T 39 S R 24 E  
379  
C 1/4  
S 35  
2003

Set a steel fence post alongside.

**79.847** The 1/4 section corner of sections 26 and 35.

---

From the 1/4 section corner of sections 35 and 36.

THE SUBDIVISION OF SECTION 35,  
T. 39 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 51.6' W., on the East - West center line of section 35.

**40.113** The center 1/4 section corner of section 35.

**80.039** The 1/4 section corner of sections 34 and 35.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

Name	Capacity
Ronald K. Baugh	Supervisory Cadastral Surveyor
Brandon Sanchez	Survey Technician
Tyler Trujillo	Survey Technician
Sterling Profazier	Survey Aid

## CERTIFICATE OF SURVEY

We, **M. Ross Workman, Cadastral Surveyor**, and **C. Scott Bishop, Survey Technician**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **21 day of March, 2003**, we have **executed the Dependent Resurvey of a portion of the old west boundary of the Navajo Indian Reservation, the east, west, and north boundaries, and the subdivisional lines, and the subdivision of sections 13, 15, 16, 17, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28 and 35, in Township 39 South, Range 24 East,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Sept. 28, 2004  
Date

M. Ross Workman  
(Cadastral Surveyor)

Sept. 28, 2004  
Date

C. Scott Bishop  
(Survey Technician)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the **Dependent Resurvey of a portion of the old west boundary of the Navajo Indian Reservation, the east, west, and north boundaries, and the subdivisional lines, and the subdivision of sections 13, 15, 16, 17, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28 and 35, in Township 39 South, Range 24 East, Salt Lake Meridian, Utah,**

executed by **M. Ross Workman, Cadastral Surveyor**, and **C. Scott Bishop, Survey Technician**, having been critically examined and found correct, are hereby approved.

September 28, 2004  
Date

Daniel W. Webb  
(Chief Cadastral Surveyor for Utah)